

## KYOCERA ECOSYS P2135dn

### Technical Spec



### General

General type	B/W desktop printer for A4 format
Technology	KYOCERA ECOSYS Laser
Engine speed	Up to 35 pages per minute A4
Resolution	Fine 1,200 dpi
Warm-up time	Approx. 16.5 seconds or less from power on
Time to first print	Approx. 8 seconds or less
Dimensions (W x D x H)	375 x 393 x 267 mm
Weight	Main unit: approx. 12 kg
Power consumption	Printing: 535 W, Stand-by: 11 W, Sleep mode: 2.5 W
Power source	AC 220 ~ 240 V, 50/60 Hz
Noise (ISO 7779 / ISO 9296)	Noise (ISO 7779 / ISO 9296) Printing in full-speed mode: 53.5 dB(A) LpA, Printing in half-speed mode: 50.2 dB(A) LpA,
Safety standards	TÜV/GS, CE - This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	Standard 256 MB, max. 1,280 MB with 1 Slot DDR2-SDRAM DIMM

## Paper Handling

Input capacity	50-sheet multi-purpose tray; 60–220 g/m <sup>2</sup> ; A4, A5, A6, B5, Letter, Legal, Folio, Oficio 2, Custom (70 x 148 – 215,9 x 356 mm) 250-sheet universal paper cassette, 60 – 120 g/m <sup>2</sup> ; A4, A5, A6, B5, Letter, Legal, Folio, Oficio 2, Custom (105 x 148 mm – 215.9 x 297 mm)
Max. input capacity with options	800 sheets A4
Duplex unit	Duplex as standard supports 60 – 105 g/m <sup>2</sup>
Output capacity	250 sheets face-down
Further information	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

## Print

Processor	PPC 465 / 500 MHz
Controller language	PRESCRIBE IIe
Emulations	PCL6 (5e, XL) incl. PJP, KPD L 3 (PostScript 3 compatible) with automatic emulation switching (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, slot for optional internal print server, PDF Direct Print, XPS
Fonts	80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417
Features	AirPrint, IPsec, HTTPS, SNMPv3, IPPS, POP over SSL, SMTP over SSL
Applicable OS (Print)	All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX, LINUX as well as other operating systems on request

## Interfaces

Standard interface	USB 2.0 (Hi-Speed), 10BASE-T / 100 Base TX / 1000 Base-T, eKUIO interface slot, SD card interface slot, USB 2.0 Host interface dedicated for USB Flash.
--------------------	---

## WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.
----------	--